

SCOTTSDALE 160

WOOD INSERTS

COUNTRY STOVES
A LIFETIME OF WARMTH



Scottsdale 160 (Arch Door, Brushed Nickel Trim & Blower)

LOG LENGTH: 18" max.
HEATING CAPACITY: 600-1,300 square feet
MAXIMUM OUTPUT: 55,600 BTU/hour
EFFICIENCY: 75%



Scottsdale 160 (Traditional Door, Black Trim)

STANDARD FEATURES

- Integrated air wash system helps keep the glass clean during use for an improved view of the fire.
- Ceramic glass for extra strength and optimum heat transfer.
- Unique, integral air wash system keeps the glass clean and clear for a wide-open view of the fire.
- Precision-cut, heavy-gauge steel provides dependable, long-lasting operation.
- High-density firebrick retains heat longer, resulting in increased efficiency.
- One-touch control ensures easy operation and comfort.
- Optional decorative door faceplates in Brushed Nickel or Nickel allow customization to your style.
- Choice of surround panels to cover the surrounding fireplace opening (1-required).
- Optional 160-CFM variable-speed blower quickly moves heat from the insert into your room.
- EPA-certified for clean and efficient operation.
- Limited Lifetime Warranty

OPTIONS

FACE STYLE & FINISH



Traditional door

- Brushed Nickel
- Nickel-Plated
- Standard Black



Arch door

SURROUND & TRIM

Choose from several sizes of surround panels and an optional black surround trim kit for a finished appearance.



Black

BLOWER

Optional variable-speed blower (160-CFM blower).



- Standard Black
- Nickel-Plated

* Square-foot heating capacities and burn times are approximations only. Actual performance may vary depending upon home design and insulation, ceiling heights, climate, condition and type of wood used, appliance location, burn rate, accessories chosen, chimney installation and how the appliance is operated.

SPECIFICATIONS

PRODUCT DIMENSIONS

	SCOTTSDALE160
Front Width	23-1/8"
Rear Width (Rear Taper Width)	23-1/2" (21-1/2")*
A = Front Height	18-1/2"
B = Rear Height	19-1/4"
C = Depth into FP	12-1/2"
Flue Diameter **	6"
D = Depth onto Hearth	6-1/2"
Approximate Weight	320 lbs.

** Consult your dealer or professional installer for recommended chimney sizes for your application. C260 and C310 require 6" reducer for use with 6" chimney.
* Leveling nuts extend outside this dimension.

CLEARANCES

		SCOTTSDALE 160
E = Insert Top to Combustible Mantel	US	24"
	Canada	26"
F = Insert Top to Top Facing	US	15"
	Canada	18"
G = Insert Side to Side Wall		20"
H = Insert Side to Side Facing		12"
I = Hearth in Front of Insert †		18"
J = Minimum Mantel Height from Bottom of Insert		43"
K = Hearth to Side of Insert		4-1/2"(US) / 8"(CN)

† In some cases the hearth depth in front of inset may be reduced by 2" for every 2" the hearth is raised. Check the owners manual for details.

SURROUND SIZING

	SCOTTSDALE 160
Surround Size	26-1/2"H x 40"W
	26-1/2"H x 48"W
	30-1/2"H x 40"W
	30-1/2"H x 48"W
Able to be Trimmed	N/A

FIREPLACE SIZING

		SCOTTSDALE 160
		MASONRY FIREPLACE
I	Minimum Depth	12-3/4"
J	Minimum Height	19-1/2"
K	Minimum Width	25-1/2"
L	Minimum Rear Width	23-1/2"
M	Maximum Lintel Depth	4-3/4"

IMPORTANT NOTES:
As with any heating appliance, fireplace or stove, this appliance is extremely hot during operation. Read and understand all operating instructions before using this appliance. For further information, consult your dealer. Actual performance may vary depending upon home design and insulation, ceiling heights, climate, condition and type of wood used, appliance location, burn rate, accessories chosen, chimney installation and how the appliance is operated. Diagrams, illustrations and photographs are not to scale-consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.

DIAGRAMS

