




## **CI1200 Cast Wood Insert**

Model	CI1200
Cordwood BTU's	55,000 BTU's
Emissions (grams/hr) EPA Certified	3.0 grams/hr
Flue Size	6" (152mm)








Minimum Fireplace Opening		
Height	19-5/8" (499mm)	
Width	25" (635mm)	
Depth: (w/ standard flue adaptor) 15-1/16" (383mm		
Depth: (w/ offset flue adaptor) 17-11/16" (449mm		





Dimension	Description	CI1200
А	Adjacent Side Wall (to side)	15" (381mm)
В	Mantle (to top)**	20" (508mm)
С	Top Facing (to top)	14" (356mm)
D	Side Facing (to side)	7-3/8" (187mm)
E Minimum Hearth Extensi	Minimum Hearth Extension*	18" (457mm) CAN
	Minimum Hearth Extension	16" (406mm) US
F	Minumim Heath Thickness*	1-1/2" (38mm)
G	Minimum Hearth Side Extension	8" (203mm)

Side and Top facing is a maximum of 1.5" thick.

Floor protection must non-combustible, insulative material with an R value of 1.1 or greater.

\* If the hearth extension is flush with the floor (F) it must extend 19.5" in front of the body face (E).

Note: Hearth Extension Width (G) is measured from edge of fuel door to side of hearth.

\*\* A non-combustible mantel may be installed at a lower height if the framing is made of metal studs covered with a non-combustible board.