

# de manincor

Manufactured by: DE MANINCOR SPA  
Italy - 38121 Trento • Via di Spini, 15  
WWW.DEMANINCOR.IT  
LISTED - COOK STOVE - WOOD BURNING

Tested by: GUARDIAN FIRE TESTING LAB.  
I.S.O. 17025 TESTING  
I.S.O. GUIDE 65 CERTIFICATION  
WWW.FIRETESTING.COM




TESTED TO: **UL-1482 ULC-S627**

MODEL / MODELE:


SERIAL N. / N. DE SÉRIE:

**MINIMUM CLEARANCES TO COMBUSTIBLE MATERIALS / DEGAGEMENT MINIMAL AUX MATERIAUX COMBUSTIBLES**  
**TOP FUEL / CARNEAU SUPERIEUR**  
**WITH SINGLE WALL CHIMNEY CONNECTOR / RACCORD DE CHEMINEE A PAROI SIMPLE**

CEILING / PLAFOND



SIDE WALL / MUR LATÉRAL



**FROM HEATER / DU POELE IN (MM)**

**A. 1 (25)**

**B. 8 (202)**

**E. 49.0 (1245)**

**FROM CHIMNEY CONNECTOR**

**DU RACCORD DE CHEMINEE IN (MM)**

**C. 18.0 (570)**

**D. 18.0 (570)**

FLOOR / PLANCHER

**FUEL - TESTED FOR WOOD. DO NOT OBSTRUCT SPACE UNDER STOVE. SPECIAL METHODS ARE REQUIRED WHEN PASSING THROUGH A WALL OR CEILING. SEE INSTRUCTIONS AND BUILDING CODES. DO NOT CONNECT THIS UNIT TO A CHIMNEY FLUE SERVING ANOTHER STOVE. FOR SAFE OPERATION, INSTALL IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. KEEP HEATER DOOR CLOSED WHILE IN OPERATION. REPLACE GLASS ONLY WITH CERAMIC GLASS.**

**PREVENT HOUSE FIRES - INSTALL AND USE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND BUILDING CODES.**

**FLOOR PROTECTION - STOVE MUST BE PLACED ON A 3/8 IN. (9.5 MM) MILLBOARD PAD OR EQUIVALENT EXTENDING 18 IN. (457MM) IN FRONT (16 IN. (406MM) IN THE U.S.) AND 8 IN. (203MM) TO THE SIDES AND REAR OF THE UNIT.**

**CHIMNEY TYPE - MINIMUM 6 IN. (152MM) DIAMETER (APPROVED FOR RESIDENTIAL USE)**

**CHIMNEY CONNECTOR - 6 IN. (152MM) DIAMETER MIN. 24 GAUGE STEEL**

**CONTACT YOUR LOCAL BUILDING OFFICIALS ABOUT RESTRICTIONS AND INSTALLATION INSPECTION. A MINIMUM CLEARANCE OF 18 INCHES (457MM) TO THE CHIMNEY CONNECTOR MAY BE REQUIRED.**

**COMBUSTIBLE - POUR USAGE AVEC BOIS. NE RIEN ENTREPOSER SOUS LE POELE. DES METHODES SPECIALES SONT REQUISES LORS DU PERÇAGE D'UN MUR OU PLAFOND. VERIFIER LES DIRECTIVES ET LES CODES DE CONSTRUCTION. NE PAS RACCORDER A LA CHEMINEE D'UN AUTRE POELE. POUR UTILISATION SECURITAIRE, SUIVRE ATTENTIVEMENT LES INSTRUCTIONS DU FABRICANT. MAINTENIR LES PORTES DU POELE FERMEES PENDANT LE FONCTIONNEMENT. REMPLACER LE VERRRE SEULEMENT AVEC DE LA CERAMIQUE.**

**PREVENEZ LES INCENDIES - INSTALLER ET UTILISER SELON LES INSTRUCTIONS DU FABRICANT ET CODES DU BATIMENT.**

**PROTEGE PLANCHERS - POELE DOIT ETRE 3/8 PO (9.5MM) INSTALLE SUR UNE PLAQUE INCOMBUSTIBLE S'ETENDANT SUR 18 PO (457MM) A L'AVANT (16 PO (406MM) E.U.) ET 8 PO (203MM) A L'ARRIERE ET SUR LES COTES.**

**TYPE DE CHEMINEE - DIAMETRE MINIMAL 6 PO (152MM) - APPROUVEE POUR USAGE RESIDENTIEL**

**RACCORD DE CHEMINEE - DIAMETRE 6 PO (152MM) EPAISSEUR CALIBRE 24 ACIER**

**CONTACTEZ VOTRE MUNICIPALITE SUR LES RESTRICTIONS ET INSPECTIONS DE L'INSTALLATION. UN DEGAGEMENT MINIMAL DE 18 PO (457MM) AU CONNECTEUR DE CHEMINEE PEUT ETRE NECESSAIRE.**

## CAUTION

**HOT WHILE IN OPERATION - DO NOT TOUCH  
KEEP CHILDREN AND CLOTHING AWAY  
CONTACT MY CAUSE SKIN BURNS  
SEE NAME PLATE AND INSTRUCTIONS  
KEEP FURNISHINGS AND OTHER  
COMBUSTIBLE MATERIALS A CONSIDERABLE  
DISTANCE AWAY FROM THE APPLIANCE  
DO NOT OVERFIRE - IF HEATER OR CHIMNEY  
CONNECTOR GLOWS, YOU ARE OVERFIRING**



## ATTENTION

**CHAUD PENDANT LE FONCTIONNEMENT - NE PASTOUCHER.  
TENIR ÉLOIGNÉS LES ENFANTS ET LES VETEMENTS - LE CONTACT  
PEU CAUSER DES BRULURES.  
CONSULTEZ LA PLAQUE D'IMMATRICULATION ET LES  
INSTRUCTIONS.  
TENIR LES FOURNITURES ET AUTRES MATIERES COMBUSTIBLES À  
DISTANCE DE L'APPAREIL.  
EVITER DE SURCHAUFFER - SI LE FEU OU LA CHEMINÉE DEVIANT  
ROUGE, VOUS SURCHAUFFEZ.**